

#### INSTALL NOTES:

1. BEND FLAT PART AS REQUIRED FOR INSTALLATION WITH AN APPROXIMATE 0.07 TO 0.20 INCH (1.8 TO 2.5 MM) RADIUS.
2. BEND MAY BE PLACED AS CLOSE AS 0.3 INCHES (7.6 MM) TO CENTER OF LED LIGHT.

#### MATERIAL:

0.032 THICK, ALUMINUM SHEET (2024-T3) ALCLAD

#### ALTERNATES:


0.032 THK TO 0.060, ALUMINUM (2024-T3, 2024-T4, 6061-T4, ASTM B 209, AMS-QQ-A-250/4/6,) OR ACCEPTABLE ALTERNATE PER FAA AC 43.13

#### UNLESS OTHERWISE SPECIFIED:

REMOVE BURRS & SHARP EDGES  
DIMENSIONS ARE IN INCHES  
TOLERANCES:  
ANGULAR: BEND  $\pm 0.5^\circ$   
TWO PLACE DECIMAL  $\pm 0.030$ "  
THREE PLACE DECIMAL  $\pm 0.010$ "

#### PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TANIS AIRCRAFT PRODUCTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TANIS AIRCRAFT PRODUCTS IS PROHIBITED.

CURRENT REV APPROVAL				DRAWN BY	GLEN OLIN	APR-27-2016	TITLE: BRACKET, 8 MM LED INDICATOR LIGHT	
				CHECKED BY	DIRK ELLIS	APR-27-2016		
				DO NOT SCALE DRAWING				
					TANIS AIRCRAFT PRODUCTS GLENWOOD MUNICIPAL AIRPORT GLENWOOD, MN 56334 USA +1.952.224.4425		SPEC: N/A	
A	INITIAL RELEASE	JUN-02-2016	GDO				SUPERCEDES: N/A	
REV	CHANGE	DATE	INIT				DRAWING: 03145	



TANIS AIRCRAFT PRODUCTS  
GLENWOOD MUNICIPAL AIRPORT  
GLENWOOD, MN 56334 USA  
+1.952.224.4425

DRAWING: 03145

SHEET 1 OF 1