NOTES

1 CABLE KIT USED WITH 115 AND 230-VOLT KITS.

A. POWER LEAD AND GROUND PINOUT DEPICTED IN SHORE POWER PLUG CONFIGURATION THIS SHEET

B. TERMINATE ARROWED WIRES AS INDICATED, REFERENCES IN PARENTHESES () MFG AND INSTALLATION NOTES.

C. WIRES MAY BE CUT AND RE-TERMINATED AND/OR CONFIGURED TO ACCOMMODATE ALTERNATE ROUTING WHEN REQUIRED.

D. FUSE NOT TO EXCEED 12 AMPS.

- E. CIRCUIT LOAD NOT TO EXCEED 80% OF CIRCUIT PROTECTION DEVICE (CPD) AMPERAGE RATING.
- F. WIRING IN PARALLEL, NEC/NEMA COLOR CODE.
- 2 SUPPLIED THROUGH NEXT HIGHER ASSEMBLY (NHA) PREHEAT KIT TOP LEVEL DRAWING.

3 PARTS SUPPLIED IN BULK.

4 CORRESPONDING RECEPTACLE PLUG ADAPTOR (OUTLET) SUPPLIED WITH 230 VOLT KIT THROUGH NHA AND WIRED ON EXTENSION CORDS PROVIDED BY OPERATOR.

